

Příklepový vrták - SDS Max

Ø 12 - 15 mm - dvě ostří,

Ø 16 - 40 mm - čtyři ostří

	Ø [mm]	ostří [mm]	vrták [mm]	
1	12,0	200	340	20 8100
1	12,0	400	540	20 8102
1	12,0	550	690	20 8104
1	14,0	200	340	20 8106
1	14,0	400	540	20 8108
1	15,0	200	340	20 8110
1	15,0	400	540	20 8112
1	16,0	200	340	20 8114
1	16,0	400	540	20 8116
1	18,0	400	340	20 8118
1	18,0	400	540	20 8120
1	20,0	200	320	20 8122
1	20,0	400	520	20 8124
1	20,0	800	920	20 8126
1	22,0	200	320	20 8128
1	22,0	400	520	20 8130
1	22,0	800	920	20 8132
1	24,0	200	320	20 8134
1	24,0	400	520	20 8136
1	25,0	200	320	20 8138
1	25,0	400	520	20 8140
1	25,0	800	920	20 8142
1	28,0	250	370	20 8144
1	28,0	450	570	20 8146
1	30,0	250	370	20 8150
1	30,0	450	570	20 8152
1	32,0	250	370	20 8154
1	32,0	450	570	20 8156
1	32,0	800	920	20 8158
1	35,0	250	370	20 8160
1	35,0	450	570	20 8162
1	35,0	550	670	20 8164
1	38,0	250	370	20 8166
1	38,0	450	570	20 8168
1	40,0	250	370	20 8170
1	40,0	450	570	20 8172
1	40,0	800	920	20 8174

Sada vrtáků do betonu - HSS - 7 ks

Ø 4 x 80; 5 x 95; 5 x 150; 6 x 100; 8 x 120; 10 x 120; 12 x 150 mm

1 20 1380

Stupňový vrták - HSS

speciální provedení pro vrtání do plechu, oceli, hliníku, nerez, PVC atd.,

maximální síla materiálu 3 mm, dřív Ø 12 mm

otvor Ø [mm]	8,0 (vrták)	12,5 (Pg 7)	14,5 (M 16)	15,2 (Pg 9)	16,5 (M 16)	18,5 (M 20)	18,6 (Pg 11)	20,4 (Pg 13,5)	20,5 (M 20)	22,5 (Pg 16)	23,5 (M 25)	25,5 (M 25)	25,8	28,3 (Pg 21)	30,5 (M 32)	32,5 (M 32)	33,6	37,0 (Pg 29)	38,5 (M 40)	40,5 (M 40)	
1 HSS	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	20 1201
1 HSS - TIN	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	20 1206
1 HSS	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	20 1200
1 HSS - TIN	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	20 1205
1 HSS	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	20 1207
1 HSS - TIN	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	20 1208
1 HSS	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	20 1209
1 HSS - TIN	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	20 1210

balení

obj. č.

